

Solarmast consist of Solar PV Modules, Solar LMLA / VRLAGel / Lifepo4 Battery, MPPT Solar charge controller DC Street light/ DC flood light & octagonal pole.

Why SolarSack's Solarmast:

- Solarmast delivers lumen efficacy of more than 110 lumen per watt, with a life of 50000hrs & IP65 ra
- Solarmast designed with PWM / MPPT charge controller which provides about 25% more charging.
- Highly efficient poly crystalline solar modules which are IEC61215, IEC61730 certified

Benifits of Solarmast:

- 1. Renewable and Independent green energy source 2. Automated switch ON and OFF.
- 3. Easy to install. Instant installation and ready to use 4. No external cabling or trenching required.
- 5. Low maintenance cost.

6. Zero Operational costs

More Advanced Features

- 1. In built No load protection, Short circuit protection, Reverse polarity protection
- 2. In build battery Reverse Polarity, Over charging, Deep discharging, Battery Temperature Compensation
- 3. Reverse polarity, Reverse current flow to PV Module during night


SS_SM_OREDA

Solar Penal: 500 wp/12v Battery : 500Ah/12, C10, LMLA/VRLA Gel, Luminary: LED 24watt.

Controller: 40A/12V PWM D2D. Pole: 7 Mtr hexagonal GI 90 & 190 4mm Thickness Base Plate


300*300*16mm, Foundation bolt: M20 * 700mm, Duty Cycle: 3 day Autonomy

Office: N4/234, IRC Village, Nayapalli, Bhubaneswar-751015 SolarSack info@solarsack.in +91 9238412384 +91 9238412394 +91 9238412399



armast Solar hiMast Street light

Solarmast Models	Solar Panel (Wp)	Batter y (Ah)	Pole & Mechanical Component	Luminary	PWM/MPP T	Auto D2D	Auto Dimming
SS_SM_ 184D	200	150 LMLA	7M, Hexagonal 3mm Thickness	18 * 4 Watt	PWM	Yes	4+8hr with Occupancy Sensor
SS_SM_ 244D	300	150 Lifepo4	7M, Hexagonal 3mm Thickness	24 * 4 Watt	PWM/MPPT	Yes	4+8hr with Occupancy Sensor
SS_SM_ 404D	480	400 LMAL	7M, Hexagonal 3mm Thickness	40 * 4 Watt	PWM	Yes	4+8hr with Occupancy Sensor



Above model having autonomy of 2days

Authorized Supplier

Office: N4/234, IRC Village, Nayapalli, Bhubaneswar-751015 SolarSack info@solarsack.in

+91 9238412384 +91 9238412394 +91 9238412399